

HYPERION FLOOD LIGHTS



13–50W




75–200W

MODEL	CODE	LED WATTS	SYSTEM WATTS	LUMENS	EFFICACY	DIMENSIONS EXCL. BRACKET	DIMENSIONS INCL. BRACKET	WEIGHT
13W	BL-CS-1100-NW	11.2W	13.4W	1320lm	110lm/W	W135 × H175 × D42mm	W150 × L205 × H42mm	1.03kg
26W	BL-CS-1101-NW	23.5W	26W	2640lm	110lm/W	W170 × H220 × D45mm	W200 × L251 × H45mm	1.87kg
50W	BL-CS-1102-NW	45.7W	50W	5280lm	110lm/W	W225 × H290 × D55mm	W243 × L330 × H55mm	3.08kg
75W	BL-CS-1103-NW	68.8W	75W	8280lm	115lm/W	W250 × H330 × D75mm	W265 × L372 × H75mm	4.8kg
120W	BL-CS-1104-NW	108W	120W	13,800lm	115lm/W	W340 × H400 × D90mm	W360 × L450 × H90mm	7.5kg
150W	BL-CS-1105-NW	138W	150W	17,250lm	115lm/W	W340 × H400 × D90mm	W360 × L450 × H90mm	7.5kg
200W	BL-CS-1106-NW	186W	200W	23,000lm	115lm/W	W340 × H400 × D90mm	W360 × L450 × H90mm	7.8kg

VOLTS	100–240V AC 50/60Hz input
POWER FACTOR	>0.95 (13W >0.90)
OPERATING TEMP.	-20°C ~ +40°C

COLOUR	Natural White 4000K
CRI	≥80
BEAM ANGLE	120° <i>Asymmetrical option available in 50–200W</i>
BRAND	≤150W Edison 2835 200W Lumileds Luxeon 3030
SOURCE LIFE	50,000 hours
SDCM	3-step MacAdam
WARRANTY	5 years

HOUSING	ADC12 aluminium with type 316 stainless steel screws and bolts NZ laboratory 1000hr salt spray test
FINISH	Black Interpon PZ660 double powder-coated <i>White and grey finishes available on request</i>
MOUNTING	4mm black powder-coated aluminium U-bracket
INGRESS PROTECTION	IP66
IK RATING	IK08
CONNECTION METHOD	2m double-insulated 3-core flex
CONTROL	Non-dimmable

COMPLIANCE	
------------	-------------------------------------------------------------------------------------

MOUNTING ACCESSORIES

ACCESSORY	CODE
MOUNTING ARM 500MM BLACK	BL-CS-ARM500B
MOUNTING ARM 800MM BLACK	BL-CS-ARM800B
MOUNTING ARM 1000MM BLACK	BL-CS-ARM1000B
STAKE 250MM BLACK	BL-CS-STAKE250B



MOUNTING ARM



STAKE