

G50 & S50 MOUNTING TRIMS



BL-DL-101-M4W



BL-DL-101-M1W



BL-DL-101-M5W
BL-DL-101-M5B



BL-DL-101-M3W



BL-DL-101-M7W



BL-DL-101-M8W



BL-DL-101-M6W



BL-DL-101-D4W



BL-DL-101-D5W



BL-DL-101-C135W
BL-DL-101-C135B

CODE	DESCRIPTION	DIMENSIONS	CUT-OUT	HOUSING	INGRESS PROTECTION
BL-DL-101-M4W	15° tilt	Ø90 × H22mm	Ø70–73mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M1W	Fixed with glass cover	Ø90 × H23mm	Ø70–73mm	White powder-coated die-cast aluminium	IP44
BL-DL-101-M5W	15° tilt and recessed	Ø105 × H22mm	Ø90mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M5B	15° tilt and recessed	Ø105 × H22mm	Ø90mm	Black powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M3W	Recessed, glare cut 25°	Ø100 × H41mm	Ø90mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M7W	15° tilt, 355° rotation, curved, and recessed	Ø110 × H35mm	Ø95mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M8W	Mini curved and recessed	Ø78 × H26mm	Ø65mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-M6W	35° tilt	W88 × H88mm	Ø80mm	White powder-coated die-cast aluminium	Indoor use only
BL-DL-101-D4W	Pin, 30° tilt with glass cover	Ø98 × H56mm	Ø90mm	White powder-coated die-cast aluminium	IP44
BL-DL-101-D5W	Slot, 30° tilt with glass cover	Ø98 × H56mm	Ø90mm	White powder-coated die-cast aluminium	IP44
BL-DL-101-C135W	For surface-mounting G50 and S50 light modules with driver	Ø135 × H207mm	-	White powder-coated spun aluminium	Indoor use only
BL-DL-101-C135B		Ø135 × H207mm	-	Black powder-coated spun aluminium	Indoor use only

FOR USE WITH G50 AND S50 MODULES
RETRO FIT PLATES ARE AVAILABLE FOR CERTAIN MOUNTING TRIMS (FOR CUT-OUTS UP TO Ø140MM)